

FG SERIES DUAL STAGE MILLS

The FG Dual Stage Mills are comprised of two Series 13 Industrial Grinders stacked one above the other.

Technical Data Comparison

Model	Housing	Shaft Diameter	Rotor Width	Rotor Diameter	Bearings	Integral Fan System	Screen Area	Shaft Speed	Tip Speed
#1320	1/2" (10mm)	2 3/4" (70mm)	12 1/2" (320mm)	24" (610mm)	2 7/16" (60mm)	16" (410mm) 2800 CFM	475 sq inches (3060 sq cm)	3600 rpm	22,600
#1340	1/2" (10mm)	3 1/4" (80mm)	17 1/2" (440mm)	24" (610mm)	2 15/16" (70mm)	16" (410mm) 3200 CFM	665 sq inches (4290 sq cm)	3600 rpm	22,600
#1360	1/2" (10mm)	3 1/4" (80mm)	20" (510mm)	24" (610mm)	2 15/16" (70mm)	18" (460mm) 4000 CFM	760 sq inches (3960 sq cm)	3600 rpm	22,600
#1380	1/2" (10mm)	3 1/4" (80mm)	24" (610mm)	24" (610mm)	2 15/16" (70mm)	20" (510mm) 5000 CFM	912 sq inches (5880 sq cm)	3600 rpm	22,600
#1390	3/4" (20mm)	5" (130mm)	36" (910mm)	24" (610mm)	3 7/16" (90mm)	C/F	1368 sq inches (8830 sq cm)	3600 rpm	22,600
#13100	1" (30mm)	6 3/8" (170mm)	48" (1220mm)	24" (610mm)	3 7/16" (90mm)	C/F	1824 sq inches (11780 sq cm)	3600 rpm	22,600