



GRAIN CLEANING EQUIPMENTS

# ANAMILLING



## AUTOMATIC DAMPENER MODEL: ACAD

Otomatik tav makinesi  
Amortissement de machine automatique  
Mojadora automática

**ANA**  
INTERNATIONAL

**ana**  
MILLING

[www.anamilling.com](http://www.anamilling.com)

## AUTOMATIC DAMPENER - MODEL: ACAD




Automatic dampening systems measure required humidity, actual humidity, specific weight, throughput capacity of grain, product temperature of grain, flowrate of water for grain dampening such as durum wheat, maize, spelt (corn) and others on request and automatically controls of the required humidity (amount of added water).

Amortissement de machine automatique sont utilisées pour augmenter la teneur en humidité du grain qui pour atteindre le taux désiré fournir correcte et au taux prévu de l'humidité du blé sortant.

L'appareil mesure l'humidité, température, le débit et le poids spécifique du grain sec entrants, et mesure également la différence de l'humidité afin d'atteindre le taux d'humidité désiré en fournissant suffisamment d'eau par des moyens de calcul de la quantité d'eau ajoutée et le poids du grain sec.

Ils sont fabriqués avec deux sections qui sont la mesure et le calcul de l'unité et l'unité de dosage.

El sistema de la mojadora automática dosifica la humedad requerida, mide la humedad real, peso específico, la capacidad de rendimiento de grano, la temperatura del grano, el caudal de agua para los mojadadores de granos como el trigo duro, el maíz, y otros de acuerdo a los requerimientos de forma automática controla la humedad requerida (cantidad de agua añadida).



MODEL	ACAD-50	ACAD-90	ACAD-220
Capacity (t/h)	1-10	5-25	22-50
	50	90	220
Dimension (mm)	700	1010	1320
A	2100	2410	2720
B	675	840	1035
C	675	840	1035
D	290	290	300
E	290	290	300
F			

"The capacities for the machines and equipments shown in this catalogue are for wheat having  $780 \text{ kg/m}^3$  specific gravity and may vary depending on the specific gravity, humidity and foreign material contents of grain"